



Produktinformation			Product information		
Produktbeskrivning: Nordic R & W H2 High med Nordic Träskärm			Product description: Nordic R & W H2 High with Nordic Wood Screen		
Harmoniserad standard: EN1317-5:2007/A2:2012			Harmonised standard: EN1317-5:2007/A2:2012		
Räcke	R H2 High	W H2 High	Safety Barrier	R H2 High	W H2 High
Kapacitetsklass	H2	H2	Containment level	H2	H2
Fordonsinträngning	VI3(1.0m)	VI4(1.1m)	Vehicle intrusion	VI3(1.0m)	VI4(1.1m)
Arbetsbredd	W2(0.7m)*	W2(0.7m)*	Working width	W2(0.7m)*	W2(0.7m)*
Skaderiskklass	B	B	Impact severity level	B	B
Motstånd mot snöplogning	4	3	Resistance to snow removal	4	3
Harmoniserad standard: EN14388:2005/AC:2008			Harmonised standard: EN14388:2005/AC:2008		
Ljudisolering	24dB		Sound insulation	24dB	
Vindlast (kN/m ²)	1.4		Wind load (kN/m ²)	1.4	
Snölast (kN)	15		Snow load (kN)	15	
Risk för fallande delar (EN 1794-2:2020)	Klass 2		Risk of falling debris (EN 1794-2:2020)	Class 2	
Beständighet:			Durability:		
Stål: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115			Steel: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115		
Trä: Royal Impregnated Pine Wood (Uncoloured)			Wood: Royal Impregnated Pine Wood (Uncoloured)		
Ståndaravstånd (m)	2.0		Post spacing (m)	2.0	
Konstruktionsbredd (m)	0.6		Construction width (m)	0.6	
Konstruktionshöjd (m)	2.2		Construction height (m)	2.2	

*Klass för räcke / Class for parapet