

DECLARATION OF PERFORMANCE (DOP)
of
HATKO NB3 ABSORPTIVE

1.Name	Noise Barrier
2.Marks	HATKO NB3 ABSORPTIVE
3.Intended Use	Road Traffic Noise Reducing Devices
4.Manufacturer	HATKO KAÜÇUK A.Ş. Merkez Mah. Akar Cad. iTower Plaza K:22 No:152 34384 Bomonti Şişli, İSTANBUL / TÜRKİYE

Essential Characteristics	Performance	Harmonized Standard
Sound Absorption, $DL\alpha$	8 dB	EN 1793-1
Airborne Sound Insulation, DLR	30 dB	EN 1793-2
Resistance to Brushwood Fire:	Class 3	EN 1794-2
Risk of Falling Debris	Class 2	EN 1794-2
Self-Weight: (panel L = 2980 mm)	Dry: 0,879 kN Reduced wet: 0,983 kN Wet: NPD	EN 1794-1
Impact of Stones	Pass	EN 1794-1
Maximum Vertical Load:	Total load: 1,8 kN	EN 1794-1
Wind and Static Load:	Design load: 1,5 kN/m ²	EN 1794-1
Dynamic Load (Snow Removal):	10 kN × 4 m ²	EN 1794-1

Performance assessed by AISICO S.r.l. - Notified Body 2131, under AVCP System 3
(Report No. 2131-AoP-CPR-065/2026), harmonized standard EN 14388:2005.

Herewith we declare that according to EN 14388 (EN 1793, EN 1794) in accordance with EU Construction Product Regulation 305/2011/EC the Noise Barrier is in conformity with the declared performance in the table above.

Signed for and on behalf of HATKO KAÜÇUK A.Ş. by:

NEJAN HATKO
CEO

Signature:

Date Of Issue: 24.06.2026